

# C Section Ladder

## 'C' Section Ladder

- Heavy duty 'C' shaped stiles with non-slip serrated round rungs
- Fully interlocking stiles for safety at extended heights
- Sections can be separated to use independently
- Can be converted to rope-operation
- Can be fitted with wall running wheels

## 'C' Section Single Ladder

Code	Closed Height	Open Height	Weight	Rungs
CS125	2.38m	-	6.00kg	9
CS130	2.88m	-	7.30kg	11
CS135	3.38m	-	8.60kg	13
CS140	3.88m	-	9.50kg	15
CS145	4.38m	-	11.30kg	17
CS150	4.88m	-	12.30kg	19
CS155	5.38m	-	13.60kg	21
CS160	5.88m	-	15.00kg	23



## 'C' Section Double Extension

Code	Closed Height	Open Height	Weight	Rungs
CD220	1.88m	3.21m	9.50kg	7
CD225	2.38m	4.21m	12.30kg	9
CD230	2.88m	5.21m	15.00kg	11
CD235	3.38m	6.21m	17.20kg	13
CD240	3.88m	7.21m	20.00kg	15
CD245	4.38m	8.21m	22.20kg	17
CD250	4.88m	9.21m	25.40kg	19
CD255	5.38m	9.96m	28.10kg	21
CD260	5.88m	10.96m	30.40kg	23

## 'C' Section Triple Extension

Code	Closed Height	Open Height	Weight	Rungs
CT320	1.88m	4.08m	14.50kg	7
CT325	2.38m	5.58m	18.10kg	9
CT330	2.88m	7.08m	22.20kg	11
CT335	3.38m	8.58m	26.30kg	13
CT340	3.88m	10.08m	29.90kg	15
CT345	4.38m	11.58m	33.60kg	17
CT350	4.88m	13.08m	37.70kg	19



## Sectional 'Surveyors' Ladders

- Interlocking sectional ladders, manufactured in oval section with serrated rungs
- Very easy to use, designed for inspection purposes only and can be easily stored in the boot of a car
- Each section is supplied with aluminium locating spigots, which are inserted into the stiles of the next section
- Safe, light ladder that can extend to 5.4 m

Code	Length	Weight	No. of sections
SU2	1.80m	4.10kg	2
SU3	2.70m	5.90kg	3
SU4	3.60m	8.20kg	4
SU5	4.50m	10.00kg	5
SU6	5.40m	11.8kg	6