

nifty

140

TRAILER MOUNTED ACCESS PLATFORM



14.25m (46ft 9in)
Working height

6.40m (21ft)
Working outreach

Hydraulic Outriggers
For quick & easy setup

**Fully Proportional
Hydraulic Controls**
Simple, reliable &
easy to maintain

Bi-Energy Available
Optimising utilisation

1.5m Wide Platform
Larger area for operator to work

150° Flyboom
Greater accuracy when
positioning platform



niftylift.com




nifty 140

The **Nifty 140** is the first of a new generation of Nifty trailer mounts taking advantage of developments in design and build technology. It delivers outstanding reach performance without compromising on functionality or quality. With one of the largest platforms in its class and a 150° flyboom, positioning is easy and hydraulic outriggers make setting up quicker than ever before.

SAFETY FEATURES

- Outriggers with Audible and Visible Alarms
- Manual Recovery with Hand Pump
- Dual Controls (Platform & Base)
- Lock Valves on all Hydraulic Cylinders
- Overrun Brakes with Gas Spring Hand Brake
- Dual Harness Points
- CE Marked



Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.



The Bi-Energy power option improves utilisation for the **140** by allowing operation in discreet and fume free environments or for extended periods where no external power source is available.



Hydraulic outriggers allow quick and easy setup and the audible alarm ensures that the operator is aware of an incorrect setup, when working in the busiest of environments.

SPECIFICATIONS

Working Height	14.25m	46ft 9in
Platform Height	12.25m	40ft 2in
Working Outreach	6.40m	21ft
Slew	360°	
Flyboom Arc	150°	
Width - Travelling	1.60m	5ft 3in
- Working	3.20m	10ft 6in
Height	2.00m	6ft 7in
Length	6.75m	22ft 2in
Weight	1,400kg*	3,100lbs*
Platform Capacity	225kg	500lbs
Platform Size	1.50m x 0.70m	4ft 11in x 2ft 4in
Control System	Fully Proportional Hydraulic	
Power System	Mains Only Battery Only Gas or Diesel Only Bi-Energy (Engine & Battery)	
Drive Option	Traction Drive	

* Weights may vary according to specification / power options, please confirm before ordering.

Supplied by:

Manufacturers of trailer mounted, self propelled and vehicle mounted platforms.

NIFTYLIFT LTD
Fingle Drive
Stonebridge
Milton Keynes
MK13 0ER
England

www.niftylift.com

e-mail: info@niftylift.com
Tel.: +44 (0) 1908 223456
Fax.: +44 (0) 1908 312733

