

**Technical Data**

Power range	1350 W
Weight in accordance with EPTA-Procedure 01/2003	10.3 kg
Rated voltage	230 V
Rated current	6.5 A
Mains frequency	50-60 Hz
Protection class	Class 2
Variable speed switch	No
Service indicator light	No
Theft protection equipped	No
AVR - Active Vibration Reduction	Yes
Chuck style	TE-S
Triaxial vibration for chiselling (concrete)	15.0 m/s <sup>2</sup>
A-weighted sound power level acc. EN 60745	101 dB (A)
A-weighted emission sound pressure level acc. EN 60745	90 dB (A)
Single impact energy (100 joules)	17 J
Hammering speed (under load 100)	2000 impacts/minute
Chiselling performance	1200 cm <sup>3</sup> /min (pointed chisel in B35 concrete)
Dimensions (LxWxH)	600 x 120 x 230 mm
Weight class	8-12 kg
Pointed chisel - Length range	
Flat chisel - Length range	
Wide-flat chisel - Width range	
Wide-flat chisel - Length range	
Channel chisel - Width range	
Bushing tool - Width range	
Tamping tool - Width range	
Earth rod rammer - Width range	
Width	120 mm
Package content	Complete with impact-resistant plastic toolbox, cleaning cloth, grease and operating instructions
Package Quantity	1
Weight	10.3 kg
Power source type	Mains mainly
Constant-on switch	Yes
Length (Imperial)	23.6 in
Length	600 mm
Width (Imperial)	4.3 in
Lifetime Service	2 years