

## D25600K Features

- Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 45 mm in diameter. Core drilling up to 100 mm
- Rotation-stop for medium-light demolition applications
- Unique dust sealing protection to prevent even the finest dust ingress into the hammer mechanism delivering high durability and extended tool life
- Hammer mechanism optimised to deliver maximum impact energy to beat frequency and efficiently drill into the hardest concrete
- Efficient mechanism delivers impact blows directly to the bit without losses through excessive vibration and rebound dampening reduces stress to the tool
- Ergonomic compact slimline design gives control and easy access to tight spaces
- Soft rubber grip handle reduces vibration to the user lowering fatigue during extensive use
- Electronic variable impact energy/speed for total control with smaller bits and light material
- Electronic brush wear indicator identifies when brushes need replacing and product should be serviced
- Unbeatable power to weight ratio: 10 J of impact energy delivered by a 6 kg hammer
- Magnesium housing for lower weight and excellent durability

## D25600K Specifications

### Specifications

<b>Specifications</b>	<b>Value</b>
Power Input	1150 Watts
Power Output	690 Watts
Load Speed	140-280 rpm
Blows per Minute	1330-2660 bpm
Impact Energy	1-10 J
Tool Holder	SDS-Max
Max. Drilling Capacity [Concrete]	45 mm
Max. Drilling Capacity [Breakthrough bit]	65 mm
Max. Drilling Capacity [Core bit]	100 mm
Weight	6.6 kg
Length	460 mm
Height	243 mm
Hand/Arm Vibration	19.0 m/s <sup>2</sup>
Uncertainty K 1 (Vibration)	2.0 m/s <sup>2</sup>
Hand/Arm Vibration - Chisel	14.0 m/s <sup>2</sup>
Uncertainty K 2 (Vibration)	1.5 m/s <sup>2</sup>
Sound Pressure	90.5 dB(A)
Uncertainty K 1 (Sound)	1.9 dB(A)
Acoustic Pressure	103.5 dB(A)
Uncertainty K 2 (Sound)	1.9 dB(A)