



## Technical Data

Ordering Name	DD EC-1 hand held combo
Rated input	1450 W
Drilling range	
Voltage	240 V
GFI	Yes
A-weighted sound power level acc. EN 60745	95 dB (A)
A-weighted emission sound pressure level acc. EN 60745	84 dB (A)
Dimensions (LxWxH)	423 x 108 x 195 mm
Weight according EPTA-Procedure 01/2003	5.7 kg
Chuck Style	Keyless chuck
Wet or Dry Cutting	Wet
Corner accessibility	46 mm
Oil flow rate - range	
Speed 1 No Load	8400 rpm
Coring range gear 1 (dry)	
Coring range gear 1 (wet)	
Coring range gear 2 (dry)	
Coring range gear 2 (wet)	
Coring range gear 3 (dry)	
Coring range gear 3 (wet)	
Coring range gear 4 (dry)	
Coring range gear 4 (wet)	
Coring range gear 5 (dry)	
Coring range gear 5 (wet)	
Coring range gear 6 (dry)	
Coring range gear 6 (wet)	
Coring range gear 7 (dry)	
Coring range gear 7 (wet)	
Coring range gear 8 (dry)	
Coring range gear 8 (wet)	
Coring range gear 9 (dry)	
Coring range gear 9 (wet)	
Coring range gear 10 (dry)	
Coring range gear 10 (wet)	
Drilling range - dry	
Drilling range - wet hand held	8 mm - 35 mm
Drilling range - wet w/ stand	
Opt. drilling range	
Opt. drilling range - dry	
Opt. drilling range - wet hand held	12 mm - 30 mm
Opt. drilling range - wet w/ stand	16 mm - 35 mm
Length	423 mm
Length (Imperial)	16.7 in
Max. core bit diameter (Imperial)	1-5/16 in

Package content	in PRCD, depth gauge, Hilti spray, cleaning cloth, impact-resistant plastic toolbox and operating instructions. Cover cap, rubber seal and PX 10 transpointer kit.
Width	108 mm
Width (Imperial)	4.3 in