

H08B**H15B-2****H15B Plus-2**

Machine weight (Cab-Rubber / Cab Steel)		kg	760 (with canopy) /-	1570 / 1620	1630 / 1680	
Dimension (length / width / height)		mm	2913 / 700-900 / 2052	3720 / 1020 / 2260	3740 / 1020-1300 / 2260	
Standard bucket capacity / width		m ³ /mm	0.022 / 350	0.05 / 450	0.05 / 450	
Engine	Model	—	Kubota D722	Mitsubishi L3E	Mitsubishi L3E	
	Displacement	cc	719	952	952	
	Rated Power	—	7.4kW / 10.0ps / 2000rpm	12.5kW / 17.0ps / 2400rpm	12.5kW / 17.0ps / 2400rpm	
	Fuel tank capacity	lit	9	20	20	
Working Range	(A) Max. digging depth (Std / Lng)	mm	1500 / -	2150 / 2350	2150 / 2350	
	(B) Max. digging height (Std / Lng)	mm	2835 / -	3250 / 3380	3250 / 3380	
	(C) Max. dumping height (Std / Lng)	mm	2010 / -	2180 / 2315	2180 / 2315	
	(D) Max vertical digging depth (Std/ Lng)	mm	1140 / -	1535 / 1705	1535 / 1705	
	(E) Max. digging radius (Std / Lng)	mm	2840 / -	3730 / 3920	3730 / 3920	
	(F) Max. reach at ground (Std / Lng)	mm	2755/ -	3635 / 3820	3635 / 3820	
	(G) Min. turning radius front	mm	1040	1235 / 1250	1235 / 1250	
	(H) Rear turning radius	mm	913	1440	1440	
	(I) Min. turning radius swing	mm	767	1140	1140	
	Boom swing angle (L / R)	deg	87 / 47	80 / 50	80 / 50	
Performance	Max. digging power Bucket / Arm (Std / Lng)	kN	8.3 / 5.9 (-)	14.4 / 8.8 (14.4 / 7.7)	14.4 / 8.8 (14.4 / 7.7)	
	Travelling speed (low / high)	km/h	2.0 / -	2.1 / 3.9	2.1 / 3.9	
	Slew speed	min ⁻¹	8.5	11.5	11.5	
Hydraulic System	Pump	Type	—	Gear 2	Gear 3	
		Oil flow quantity	lit/min	10.2 / 10.2	15.7 / 15.7 / 15.7	15.7 / 15.7 / 15.7
	PTO	Oil flow quantity	lit/min	20.4	31.4	31.4
		Main relief pressure	MPa	16.2 / 16.2	18.6 / 18.6 / 18.6	18.6 / 18.6 / 18.6
		Hyd. tank capacity	lit	13	24	24