


JCPT(DC)

Self-Propelled Rough-Terrain Scissor Lifts





Standard equipment

- Proportional controls
- Self-lock gate on platform
- Drivable at full height
- Foam-filled tyre
- 2WD
- Automatic brakes system
- Emergency lowering system
- Emergency stop button
- Cylinder holding valve
- Onboard diagnostic system
- Tilt sensor with alarm
- All Motion Alarm
- Horn
- Safety brackets
- Hour meter
- Folding guardrails
- Extended Platform
- Flashing beacon
- Hydraulic oil cooler
- Oscillating Axle
- Forklift Pockets

Options

- Automatic leveling hydraulic outriggers
- Overload sensor with alarm
- Non marking tyres
- Hydraulic water pump
- Platform work lights
- AC power to platform



JCPT1218DC

JCPT1418DC

	S.W.L	454kg	363kg
	S.W.L On Extension	136kg	136kg
	Max.Occupants	4	3
	A Max.Working Height	12.00m	14.30m
	B Max.Platform Floor Height	10.00m	12.30m
	C Overall Length(With/Without Outriggers)	3.84m/3.19m	3.84m/3.19m
	D Overall Width	1.76m	1.76m
	Overall Height(Rails Up)	2.59m	2.74m
	E Overall Height(Rails Down)	1.82m	1.97m
	Platform Size(Length/Width F)	2.88m×1.52m	2.88m×1.52m
	G Platform Extension Size	1.43m	1.43m
	Ground Clearance	0.24m	0.24m
	H Wheelbase	2.29m	2.29m
	Turning Radius(Inside/Outside)	2.15m/4.85m	2.15m/4.85m
	Drive Motor	2×32VAC/3.3kw	2×32VAC/3.3kw
	Lifting Motor	48V/7.8kw	48V/7.8kw
	Travel Speed(Stowed)	6km/h	6km/h
	Travel Speed(Raised)	0.48km/h	0.48km/h
	Up/Down Speed	40/46sec	45/46sec
	Gradeability	40%	40%
	Max.Working Slope(ANSI)	2°/3°	2°/3°
	Max.Working Slope(CE)	1.5°/3°	1.5°/3°
	Batteries	8×6V/315Ah	8×6V/315Ah
	Integrated Charger	48V/25A	48V/25A
	Hydraulic Tank	71L	71L
	Tyres	26×12-16.5	26×12-16.5
	Weight(With/Without Outriggers)	4400kg/4135kg	5150kg/5150kg



Oscillating Axle



Safety Bracket



Folding Guardrails



Emergency Lowering System



Automatic Leveling Outriggers



Extended Platform



Batteries



Gradeability