

## Specifications

### MODELS »

#### 9HP Pro DR Stump Grinder

#### 6HP Premier DR Stump Grinder



<b>Manufacturer</b>	DR Power Equipment	DR Power Equipment
<b>Model</b>	9 HP Pro Stump Grinder	6 HP Premier Stump Grinder
<b>ENGINE</b>		
<b>Make/Model</b>	Subaru EX 27 - 9hp	Subaru SP 170 - 6hp
<b>Max Horsepower</b>	9 @ 4000 rpm	6 @ 4000 rpm
<b>Torque</b>	13.74 ft. lbs. @ 2500 RPM	8.34 ft. lbs. @ 2500 RPM
<b>Displacement</b>	265 cc	169 cc
<b>Rings/Cylinders</b>	HD piston rings & cast iron cylinder liner	HD piston rings & cast iron cylinder liner
<b>Type</b>	Electronic spark ignition, overhead cam, 4-cycle	Electronic spark ignition, overhead cam, 4-cycle
<b>Cam</b>	Case hardened steel chain driven overhead cam	Case hardened steel chain driven overhead cam
<b>RPM Speeds</b>	Idle: 1400RPM Max 3600RPM	Idle: 1400RPM Max 3600RPM
<b>Cooling Method</b>	Air	Air
<b>Fuel Tank Capacity</b>	1.59 U.S. Gallons	.90 U.S. Gallons
<b>Oil Capacity</b>	33.8 Fl. oz.	20.3 Fl. oz.
<b>Decompression</b>	Automatic	Automatic
<b>Crankshaft</b>	Dual ball bearing crankshaft support	Dual ball bearing crankshaft support
<b>Starting</b>	Pull	Pull
<b>Air Cleaner</b>	Single Element	Single Element
<b>Lubrication</b>	Splash	Splash
<b>CLUTCH</b>		
<b>Model</b>	Noram 4000 series	Noram 4000 series
<b>Bearings</b>	Radial ball bearing support	Radial ball bearing support
<b>BELT</b>		
<b>Model</b>	Carlisle BP47	Carlisle AP47
<b>Construction</b>	Wrapped Construction for abrasion resistance	Wrapped Construction for abrasion resistance

**CUTTING HEAD**

<b>Construction</b>	Dual Ball bearing support	Dual Ball bearing support
<b>Thickness</b>	1/2"	1/2"
<b>Diameter</b>	10.5"	10.5"
<b>Number of Teeth</b>	9 (replaceable)	9 (replaceable)
<b>Tooth RPM</b>	2789 RPM	2789 RPM
<b>Tooth Speed</b>	88 MPH	88 MPH

**FRAME**

<b>Construction</b>	Fully welded 12 ga steel construction Optimized Using FEA for Strength	Fully welded 12 ga steel construction Optimized Using FEA for Strength
<b>Deck</b>	11- gauge steel	11- gauge steel
<b>Paint</b>	Powder coat	Powder coat

**HANDLEBARS**

<b>Height</b>	Adjustable	Adjustable
---------------	------------	------------

**CONTROLS**

<b>Operator Presence System</b>	Yes	Yes
<b>Throttle</b>	Yes	Yes
<b>Wheel Brake with Lock</b>	4" Band Brake with Locking Feature	4" Band Brake with Locking Feature

**WHEELS**

<b>Tires</b>	15" x 4.5" lugged	15" x 4.5" lugged
<b>Wheels</b>	Steel	Steel

**AXLES**

<b>Size</b>	Oversized 3/4	Oversized 3/4"
-------------	---------------	----------------

**WEIGHT**

<b>Machine Weight</b>	139 lbs.	125 lbs.
-----------------------	----------	----------