

## F435-DV

Model	F435-DV
Supply Voltage	230 / 110V Selectable
Type	Standard Refrigerant
Water Removal (Max)	48 L / day (32.2°C/90%RH)
Water Removal (AHAM)	25 L / day (26.7°C/60%RH)
Water Removal (EU standard)	42.6 L / day (30°C/80%RH)
Water Removal (EU standard)	21 L / day (20°C/60%RH)
Amp Draw	3.3 A (230V) - 6.5 A (110V)
Power Consumption	0.72KW / Hour (110V) 0.76KW / Hour (230V)
Operating Temperature Range	1° - 38°C
Operating Humidity Range	40 - 100%
Dimensions (H × W × D)	85 × 50 × 51 cm
Use Weight	39 KG
Air movement	350 M <sup>3</sup> /Hr
Controls	Manual Rotary On/Off
Hour Counter	Yes
Killowatt Meter	Yes
Humidistat	Yes (30-70%)
Adjustable Defrost Setting	No
Remote Monitoring Capability	No
Refrigerant Type	410A
Defrost Type	Reverse Cycle
Average Noise Level	db
Condensate Removal	Automatic Pumpout - Centrifugal
Drain Hose Length	12.2 M
Condensate pump lift capacity	2 m
Power Cord Length	5 M
Plug Type	13A 3 Pin BS1363 - 230V 16A 3 Pin BS4343 - 110V
Air Filter	Fibreglass
Microban® Protected	Yes - Cover
Wheels	30cm Semi-pneumatic
Handle	Rigid
Cable & Hose Storage	Yes
Stackable	No
Safety Mark	CE
Product Warranty	2 years - limited
Refrigeration System Warranty	6 years
Housing Warranty	Rotomoulded Cover - Lifetime