

SSD10000 10.0kVA / 8.0KW / KUBOTA D722 / AVR Controlled

Standard Features : (Shown with 2 wheel trolley option) Electric Key Start Kubota watercooled diesel engines, complete with high engine temperature shutdown and low oil pressure shutdown / Super silent close fitting skid mount acoustic cabinets with large access doors for ease of maintenance, trolley options available as shown / Dual voltage output complete with overload protection / AVR controlled as standard (SSD 10000 only) / RCD / ELCB fitted to 230 volt output (SSD 10000 only) / Brushless maintenance free Mecc Alte alternators / Integral long range fuel tanks giving up to 13 hours running at 75% load

Specifications

10kVA SUPER SILENT DIESEL GENERATING SET (3000rpm)

OUTPUT:

10kVA (8.0kW), 50Hz, 115 & 230 volt, single phase.

CONTROL PANEL:

Key start / stop, MCB, RCD 230v, low oil, high engine temperature, and low battery warning lights. Hours run meter. Fuel gauge. Emergency stop switch, BS4343 industrial sockets; 1x16a & 2x32a 115v, 2x16a & 1x32a 230v.

ENGINE:

Kubota D722, 2 cylinder water cooled diesel. Electric start/stop with low oil pressure and high engine temperature shutdown. 12v battery charging system.

ALTERNATOR:

Mecc Alte PE28 AVR controlled brushless maintenance free alternator, single bearing.

FUEL TANK:

Integral 37litre tank giving 13hours continuous use at 75% load.

CANOPY:

Steel panelled acoustic / weather-proof enclosure with large lockable access doors for maintenance. Heavy duty hinges. Lifting beam / eye. Mild steel powder coat finish.

NOISE LEVEL:

69dB (A) @ 7 metres. 94LWA

SIZE:

L1210 x W655 x H900mm

WEIGHT:

355kg (dry).