















9 - 45 kVA FUEL OPTIMISED

											
Model		G8X	G8QX	G13X	G13QX	G17X	G17QX	G33X	G33QX	G45X	G45QX
Type - Open, Canopy, Container		Open	Canopy	Open	Canopy	Open	Canopy	Open	Canopy	Open	Canopy
Engine make		Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder
Prime power (PRP) at 50Hz 400V	kVA	8	8	12	12	17	17	34	34	41	41
Standby power (ESP) at 50Hz 400V	kVA	9	9	13	13	18	18	37	37	45	45
Prime power (PRP) at 60Hz 480V	kVA	10	10	15	15	20	20	40	40	50	50
Standby power (ESP) at 60Hz 480V	kVA	11	11	17	17	22	22	44	44	55	55
Length	mm	1450	1475	1450	1475	1450	2100	1850	2100	1850	2100
Width	mm	1286	1104	1286	1104	620	975	780	975	780	975
Height	mm	620	750	620	750	1286	1349	1500	1349	1500	1349
Weight including oil and water	kg	279	456	369	506	409	765	579	909	626	944









22 - 46 kVA STAGE IIIA

							
Model		G22X	G22QX	G34X	G34QX	G46X	G46QX
Type - Open, Canopy, Container		Open	Canopy	Open	Canopy	Open	Canopy
Engine make		Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder	Yanmar 3-cylinder
Prime power (PRP) at 50Hz 400V	kVA	20	20	34	34	41	41
Standby power (ESP) at 50Hz 400V	kVA	22	22	37	37	46	46
Length	mm	1700	2100	1850	2100	1850	2100
Width	mm	620	975	780	975	780	975
Height	mm	1286	1349	1500	1349	1500	1349
Weight including oil and water	kg	452	800	579	950	614	844







63 - 138 kVA FUEL OPTIMISED

									
Model	G65X	G65QX	G90X	G90QX	G115X	G115QX	G140X	G140QX	
Type - Open, Canopy, Container	Open	Canopy	Open	Canopy	Open	Canopy	Open	Canopy	
Engine make	JCB	JCB	JCB	JCB	JCB	JCB	JCB	JCB	
Prime power (PRP) at 50Hz 400V	kVA	59	59	80	80	108	108	125	125
Standby power (ESP) at 50Hz 400V	kVA	63	63	88	88	119	119	138	138
Prime power (PRP) at 60Hz 480V	kVA	65	65	85	85	106	106	125	125
Standby power (ESP) at 60Hz 480V	kVA	72	72	94	94	117	117	138	138
Length	mm	2150	2750	2150	2750	2150	2750	2450	2750
Width	mm	780	1100	780	1100	1160	1100	795	1100
Height	mm	1492	1760	1492	1760	1506	1760	1590	1760
Weight including oil and water	kg	1110	1590	1110	1590	1168	1690	901	1720

60 - 130 kVA STAGE IIIA

									
Model	G66X	G66QX	G91X	G91QX	G116X	G116QX	G141X	G141QX	
Type - Open, Canopy, Container	Open	Canopy	Open	Canopy	Open	Canopy	Open	Canopy	
Engine make	JCB	JCB	JCB	JCB	JCB	JCB	JCB	JCB	
Prime power (PRP) at 50Hz 400V	kVA	60	60	80	80	105	105	130	130
Standby power (ESP) at 50Hz 400V	kVA	68	68	88	88	116	116	143	143
Length	mm	2150	2750	2810	2810	2150	2750	2450	2750
Width	mm	780	1100	1150	1150	1160	1100	795	1100
Height	mm	1492	1760	1793	1793	1506	1760	1590	1760
Weight including oil and water	kg	1110	1590	1720	1720	1168	1690	1078	1825

143 - 220 KVA FUEL OPTIMISED

						
Model	G144X	G144QX	G175X	G175QX	G220X	G220QX
Type - Open, Canopy, Container	Open	Canopy	Open	Canopy	Open	Canopy
Engine make	IVECO	IVECO	IVECO	IVECO	IVECO	IVECO
Prime power (PRP) at 50Hz 400V	kVA 131	kVA 131	kVA 159	kVA 159	kVA 200	kVA 200
Standby power (ESP) at 50Hz 400V	kVA 143	kVA 143	kVA 175	kVA 175	kVA 220	kVA 220
Prime power (PRP) at 60Hz 480V	kVA 145	kVA 145	kVA 173	kVA 173	kVA 227	kVA 227
Standby power (ESP) at 60Hz 480V	kVA 159	kVA 159	kVA 189	kVA 189	kVA 249	kVA 249
Length	mm 2900	mm 3300	mm 2900	mm 3300	mm 2900	mm 3300
Width	mm 900	mm 1200	mm 900	mm 1200	mm 900	mm 1200
Height	mm 1600	mm 1958	mm 1603	mm 1958	mm 1634	mm 1958
Weight including oil and water	kg 1412	kg 2301	kg 1450	kg 2400	kg 1521	kg 2517











275 – 590 kVA FUEL OPTIMISED

								
Model	G275X	G275QX	G330X	G330QX	G400X	G400QX	G440X	G440QX
Type - Open, Canopy, Container	Open	Canopy	Open	Canopy	Open	Canopy	Open	Canopy
Engine make	Scania	Scania	Scania	Scania	Scania	Scania	Scania	Scania
Prime power (PRP) at 50Hz 400V	kVA 250	250	300	300	350	350	400	400
Standby power (ESP) at 50Hz 400V	kVA 275	275	330	330	400	400	450	450
Prime power (PRP) at 60Hz 480V	kVA 282	282	330	330	424	424	460	460
Standby power (ESP) at 60Hz 480V	kVA 305	305	360	360	462	462	501	501
Length	mm 3000	3800	3800	3800	3600	4500	3600	4500
Width	mm 1160	1400	1400	1400	1460	1800	1460	1800
Height	mm 1759	2290	2290	2290	2090	2340	2090	2340
Weight including oil and water	kg 2172	3936	3647	3647	2678	4388	2814	4524

275 – 590 kVA FUEL OPTIMISED

								
Model	G500X	G500QX	G545X	G545QX	G550X	G550QX	G600X	G600QX
Type - Open, Canopy, Container	Open	Canopy	Open	Canopy	Open	Canopy	Open	Canopy
Engine make	Scania	Scania	Scania	Scania	Scania	Scania	Scania	Scania
Prime power (PRP) at 50Hz 400V	kVA 461	461	505	505	502	502	550	550
Standby power (ESP) at 50Hz 400V	kVA 501	501	552	552	550	550	590	590
Prime power (PRP) at 60Hz 480V	kVA 500	500	500	500	500	500	552	552
Standby power (ESP) at 60Hz 480V	kVA 548	548	548	548	545	545	600	600
Length	mm 3600	4500	3600	4500	3600	4500	3600	4500
Width	mm 1460	1800	1460	1800	1460	1800	1460	1800
Height	mm 2090	2340	2090	2340	2090	2340	2090	2340
Weight including oil and water	kg 2917	4627	3047	4757	3313	5023	3313	5023

250 - 550 kVA STAGE IIIA









								
Model	G276X	G276QX	G331X	G331QX	G401X	G401QX	G441X	G441QX
Type - Open, Canopy, Container	Open	Canopy	Open	Canopy	Open	Canopy	Open	Canopy
Engine make	Scania	Scania	Scania	Scania	Scania	Scania	Scania	Scania
Prime power (PRP) at 50Hz 400V	kVA 250	250	300	300	350	350	400	400
Standby power (ESP) at 50Hz 400V	kVA 275	275	330	330	400	400	450	450
Length	mm 3000	3800	3000	3800	3600	4500	3600	4500
Width	mm 1160	1400	1160	1400	1460	1800	1460	1800
Height	mm 1759	2290	1759	2290	2090	2340	2090	2340
Weight including oil and water	kg 2172	3434	2385	3647	2678	4388	2814	4524

250 - 550 kVA STAGE IIIA





				
Model	G551X	G551QX	G601X	G601QX
Type - Open, Canopy, Container	Open	Canopy	Open	Canopy
Engine make	Scania	Scania	Scania	Scania
Prime power (PRP) at 50Hz 400V	kVA 501	501	550	550
Standby power (ESP) at 50Hz 400V	kVA 550	550	590	590
Length	mm 3600	4500	3600	4500
Width	mm 1460	1800	1460	1800
Height	mm 2090	2340	2090	2340
Weight including oil and water	kg 3371	5081	3371	5081







278 - 510 kVA STAGE IIIA

									
Model		G306X	G306QX	G336X	G336QX	G406X	G406QX	G446X	G446QX
Type - Open, Canopy, Container		Open	Canopy	Open	Canopy	Open	Canopy	Open	Canopy
Engine make		MTU	MTU	MTU	MTU	MTU	MTU	MTU	MTU
Prime power (PRP) at 50Hz 400V	kVA	278	278	300	300	350	350	400	400
Standby power (ESP) at 50Hz 400V	kVA	306	306	330	330	400	400	446	446
Length	mm	3310	4100	3310	4100	3600	4500	3600	4500
Width	mm	1390	1600	1390	1600	1602	1800	1602	1800
Height	mm	2061	2200	2061	2200	2121	2340	2121	2340
Weight including oil and water	kg	3069	4531	3096	4531	3496	5232	3632	5368

278 - 510 kVA STAGE IIIA

					
Model		G506X	G506QX	G566X	G566QX
Type - Open, Canopy, Container		Open	Canopy	Open	Canopy
Engine make		MTU	MTU	MTU	MTU
Prime power (PRP) at 50Hz 400V	kVA	460	460	510	510
Standby power (ESP) at 50Hz 400V	kVA	507	507	562	562
Length	mm	3600	4500	3600	4500
Width	mm	1602	1800	1602	1800
Height	mm	2121	2340	2121	2340
Weight including oil and water	kg	3872	5582	4002	5712

659 - 728 kVA FUEL OPTIMISED

				
Model	G656X	G656QX	G726X	G726QX
Type - Open, Canopy, Container	Open	Canopy	Open	Canopy
Engine make	MTU	MTU	MTU	MTU
Prime power (PRP) at 50Hz 400V kVA	600	600	663	663
Standby power (ESP) at 50Hz 400V kVA	659	659	728	728
Prime power (PRP) at 60Hz 480V kVA	635	635	693	693
Standby power (ESP) at 60Hz 480V kVA	694	694	763	763
Length mm	3600	5000	3600	5000
Width mm	1604	2100	1604	2100
Height mm	2121	2369	2121	2369
Weight including oil and water kg	4529	6739	4671	6881

