

WSJ 750-ET (110V)



Technical Data

Weight	2.6 kg
Outside Diameter of Extraction Connector	30 mm
Aluminum Cutting Range	Up to 25 mm
Cutting Depth at 0 Degrees	Wood: 4-11/16 in. Mild Steel: 3/8 in. Aluminum: 1 in. Stainless : 1/2 in.
Input power	750 W
No Load Speed	900 - 3000 rpm
Max Stroke Rate No Load	3000 str./min
Metal Cutting Range	Up to 10 mm
Output Power	7.8
Timber Cutting Range	Up to 120 mm
Rated voltage	110 V
Additional product information	Stroke: 28 mm
	Bevel cuts (left/right): 0-45°
	Blade connection end: T-shank
Max Angle	45 °
Min Angle	0 °
Number of Orbital Action Settings	4
Orbital Action	Yes
Protection Class	Protection class II (double insulated)
Min Stroke Rate No Load	900 str./min
Base materials	Wood, Metal, Plastic, PVC, Plaster plates, Plastified fibres
Radio and TV Interference Suppression	As per EN 50144
Package content	Equipped with low friction base plate cover, dust extraction conn insert, dust extraction cover, W-CSJ W 73/4 HCS ParallelCut saw operating instructions and safety precautions. Supplied in Hilti pl resistant toolbox
Package Quantity	1
Approvals	CE, CSA