The LUX 350N is the floor saw for light repair and maintenance jobs on industrial floors and roads. It is light, compact, easy to handle and fitted with a Honda 5.9 kW petrol engine.



CONSTANT CUTTING DEPTH

The cutting depth adjustment handwheel is fitted with a lock to withstand vibrations and prevent the cutting depth from being changed inadvertently.

CONTROL PANEL

The panel includes the selector for turning the engine on and off, the cutting adjustment handwheel and the oil level gauge.

BLADE GUARD WITH WATER SYSTEM

The blade guard includes hoses for wetting with water. A continuous flow is needed to cool the blade and prevent the formation of dust that would be harmful for the operator.

REMOVABLE AND HEIGHT-ADJUSTABLE HANDLE BAR

OPTIONAL WATER TANK

The optional 10 litre water tank can be used to wet the blade on road sites or in places where a suitable water supply is not available.

PROTECTION BAR

The steel bar protects the motor and is a convenient lifting point.

DRIVE WITH HIGH STRENGTH TOOTHED BELTS

WATER VALVE Using the water valve it is possible to connect to the source of water and adjust the flow.

HINGED BLADE COVER

The front of the blade cover can be raised for cutting walls and kerbs.

RUBBER WHEELS WITH BALL BEARINGS

The rubber wheels with special ball bearings prevent sideways movement which would adversely affect the blade and cutting quality.

BLADE AND TOOL KIT HOLDER

The tool kit holder also adjust the blade during transport.

EASIER MAINTENANCE

The engine oil drain tube is on the outside to simplify routine maintenance operations.