



## Shears GSC 2.8

The slim tool with reversible blade

- Slim design with planetary gears
- Reversible blade for particularly high economic efficiency
- Knob grip for comfortable and safe guidance



- Tight curve radius for flexible cuts
- Sliding switch adapted to grip and covered
- Optimum view of cutting line
- Sturdy design for continuous use
- Powerful 500-watt motor
- Safety switch

### Part no. 0 601 506 142

- Blade (2 607 010 025)
- Alignment gauge (ET no. 2 607 970 001)
- Allen key KW 5 (ET no. 1 907 950 006)
- Allen key KW 2.5 (ET no. 1 907 950 003)

---

Package (L/W/H)	325 x 170 x 90 mm
-----------------	-------------------

---

Voltage, electrical	230 V
---------------------	-------

---

### Technical data

---

Material that can be processed	Steel up to 400 N/mm <sup>2</sup> at 2.8 mm
--------------------------------	---------------------------------------------

---

Stroke rate, load	1.500 spm
-------------------	-----------

---

Stroke rate at no load	2.400 spm
Weight without cable	2,7 kg
Length	292 mm
Height	205 mm

**Maximum cut thicknesses**

Steel up to 400 N/mm <sup>2</sup>	2,8 mm
Steel up to 600 N/mm <sup>2</sup>	2,2 mm
Steel up to 800 N/mm <sup>2</sup>	1,9 mm
Aluminium up to 200 N/mm <sup>2</sup>	3,5 mm

**Electric specifications**

Rated power input	500 W
Power output	270 W