

## **POWERCENTER 15 GENERATOR**

## **ALTERNATOR**

Three Phase	Rated Output Rated Voltage Rated Current Power Factor	(kVA) (V) (A)	15 415 20.9 0.8
Single Phase	Rated Output Rated Voltage Rated Current Power Factor	(kVA) (V) (A)	15/12 240/110 50/109.1 1.0
Rated Frequency Excitation Number of Poles		(Hz)	50 Brushless 2

- Fully bunded
- Multi-voltage
- Super silent
- Compact design

## **ENGINE**

Model Rated Speed Fuel	(Kubota) (min-1)	D902 3000 Diesel
Fuel Tank Capacity	(L)	37
Fuel Consumption	(L/Hr)	3.5
Lubricant Capacity	(L)	3.6
Coolant Capacity	(L)	4.0

## **SET**

<u> </u>			
Dry Weight		(kg)	390
Length		(mm)	1,410
Width		(mm)	635
Height		(mm)	780
Noise		(dB*A/7m)	63.5
		(LWA*dB)	91.5
Bunded			YES
Emergency Stop			YES
Digital Display			YES
Outputs	Three Phase	(415V)	1 x 32Amp
	Single Phase	(240V)	2 x 32Amp 1 x 16Amp
	Single Phase	(110V)	2 x 32Amp 1 x 16Amp
	Hard Wire/Terminal Board		YES



