

#### GENERATOR SPECIFICATION

<b>Voltage</b>	230/115
<b>Phase</b>	1
<b>Frequency</b>	50Hz
<b>Prime Power (PRP)</b>	4.0kVA / 3.2kW
<b>Alternator</b>	NSM K100F
<b>Alternator Type</b>	Brushless - Smooth Waveform
<b>Fuel tank capacity</b>	13.0 Litres
<b>Autonomy 75% load</b>	13.0 Hours
<b>LWA</b>	96
<b>dBA @ 7M</b>	71

#### ENGINE SPECIFICATION

<b>Engine</b>	Lombardini 15LD 350S
<b>Emissions certified</b>	N/A
<b>Cylinders</b>	Single
<b>Distribution</b>	O.H.V.
<b>Aspiration</b>	Normally aspirated
<b>Cooling</b>	Air
<b>Displacement</b>	349 cm <sup>3</sup>
<b>Rpm</b>	3000
<b>Starting system</b>	Key - Electric start
<b>Fuel</b>	Diesel



#### DIMENSIONS (mm)

DIMENSIONS (mm)			WEIGHT (KG)
Length	Width	Height	92
775	475	560	



#### CONTROL BOX

- 1 x 16A & 1 x 32A 115V BS4343 sockets.
- 1 x 16A 230V BS4343 socket.
- Reset circuit breaker overload protection.

#### STANDARD FEATURES

- Key start.
- Low oil pressure & battery charge fail warning lamps.
- Long run fuel tank.
- Easy carry fold-away handles.
- Brushless smooth waveform alternator.

#### OPTIONS

- Single voltage.
- Trolley kit.

#### POWER DEFINITION

##### Prime Power (PRP) :

Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1.